

# SAFETY DATA SHEET (SDS)



MINERAL X - RTU

RUST, SCALE, & MINERAL CLEANER BLEND OF ORGANIC SALTS / DEGREASERS Date Revised : 05 / 15 Supercedes : 03 / 09 SAFER ALTERNATIVE TO ACID -BASED MINERAL CLEANERS REMOVES HARD WATER STAINS

"MINERAL X " - RTU : Rust, Scale, & Mineral Cleaner

A safer, reduced toxicity alternative to harsh acid-based mineral cleaners. With a unique blend of organic salt and degreasing agents, tough iron & mineral deposit build-ups , hard water stains, and calcium deposits are easier than ever to remove. Use on a wide variety of surfaces to remove soils & stains like : Brick ; Ceramic Tile ; Fiberglass ; Grout ; Polished Metals Sinks, Toilets, and other Porcelain Fixtures ;

Showers, & Stainless Steel more.

CHEMTREC :1-800-424-9300 (ref. : Core )

HEALTHY CLEAN BUILDINGS

4 Wilmington Drive Melville, New York 11747

Refer to Product Label

1-631-643-1882

### SECTION 1 : IDENTIFICATION OF SUBSTANCE / COMPANY

### PRODUCT NAME / IDENTIFIER :

PRIMARY APPLICATION / RECOMMENDED USAGE :

DISTRIBUTED EXCLUSIVELY BY :

INFORMATION TELEPHONE : EMERGENCY TELEPHONE ( 24 hour ) : USAGE RESTRICTIONS :

#### SECTION 2 : HAZARD(S) IDENTIFICATION

While this product is not considered hazardous, this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be made available to users of this product. Prolonged or repeated skin contact in an occupational setting may result in irritation and in these situations, the use of chemical resistant gloves is recommended. This product is not regarded as a mutagen or carcinogen, and there is low concern for reproductive, developmental, or nervous system toxic effects.

#### Classification of the substance or mixture (GHS-US)

Skin Irritation 2	H315
Eye Damage 1	H318
Skin Sensitivity 1	H317
Label Elements	
Hazard Pictograms	Skin & Eye Irritant
(GHS-US Labeling)	Respiratory Tract Irritant
Signal Word : Hazard Statements :	Warning H315 – May cause Skin Irritation as a water diluted product . H317 – May cause an allergic skin reaction . H318 – May cause serious eye irritation as a diluted product .

MINERAL X page 1



## SAFER ALTERNATIVE TO ACID -BASED MINERAL CLEANERS REMOVES HARD WATER STAINS

HAZARD ( S ) IDENTIFICATION ( continued )			
Precautionary Statements	P261 – Avoid breathing dust / mist/ spray .		
	P264 - Wash hands and forearms thoroughly after handling		
•	P280 – Wear Protective gloves / eye protection		
	P302 + P352 – If on skin, wash with plenty of soap and water		
• 1 B	P305+P351+P338 – If in eyes, rinse cautiously with water for several minutes .		
•	If easy to do, remove contact lenses .Continue rinsing		
	P337+P313 – If eye irritation persists, get medical advice/attention.		
	P310 – Immediately call a poison center / doctor .		
•	P321 – Specific treatment ( see First Aid Measures on Product Label / SDS )		
	P332+P313 – If skin irritation occurs, get medical advice / attention		
*	P333+P313 – If skin irritation or rash occurs, get medical advice / attention		
¥.	P362+P364 – Take off contaminated / soiled clothes and wash before reuse		
. ,	P501 - Dispose of contents / container in accordance with local / regional/ national / int'l regulations		

Other Hazards : None Ingredients with Unknown Acute Toxicity : Not Established

#### SECTION 3 : COMPOSITION / INFORMATION ON INGREDIENTS :

Chemical characterization : Diluted Mixture with water .

Hazardous Components :				
Ingredient :	CAS Number :	Percent :	OSHA / PEL :	ACGIH / TLV :
Carbamide (Urea) Hydrochloride	506 - 89 - 8	< 4%	NE	NE 5 ppm

NOTE : Approximate percentages - Exact percentages and identities are withhold as trade secrets

#### **SECTION 4 : FIRST AID MEASURES**

**Description of Necessary Measures :** 

Relevant Routes of Exposure : Skin Contact , Eye Contact , Ingestion

After Skin Contact : Classified as a skin irritant ( as per the 1992 OECD Guideline for Chemical Testing , # 404 :"Acute Dermal Irritation / Corrosion " ) . Wash with plenty of soap and water ; followed by a warm water rinse . Apply a topical antiseptic agent to open wounds or broken skin . Remove contaminated clothing and shoes . Launder soiled , contaminated clothing before reuse . If skin irritation or rash persists , seek medical attention ( P332+P313 ) .

After Eye Contact : May cause serious eye irritation after prolonged exposure .Rinse cautiously with warm running water for 15 minutes, lifting upper and lower lids occasionally .. If easy to do, remove contact lenses .Continue water rinsing . ( P 305+P351+P338 If eye irritation persists such as blinking, redness, or pain, seek medical attention . (P337 + P313).

After Ingestion: May be harmful if swallowed. Do Not Induce vomiting unless advised by a physician or poison control center. If patient is fully conscious, continue to rinse mouth with water and drink 2-3 glasses of water. If adverse conditions persist, seek medical attention. Never give anything by mouth if victim is unconscious, rapidly losing consciousness, or is convulsing. Call a Poison Control Center / Doctor / Physician, if necessary (P312).

**After Inhalation :** May be irritating to respiratory system if inhaled as a mist .Move to fresh air . Keep individual at rest in a position comfortable for breathing .If not breathing, give artificial respiration . If breathing is difficult, administer oxygen and seek medical attention (P261).

Note to Physicians (Both acute and delayed symptoms): Breathing difficulty, coughing, cramp, nausea, acidosis, disorientation. Extreme caution regarding gastric perforation; pulmonary edema; impaired breathing; & disturbed cardiac rhythm. Potential symptoms of poisoning may occur after several hours of exposure. It is advised that at least 48 hour medical observation take place after the incident, especially for pneumonia and pulmonary edema. In case of irritation to lungs, initially treat with cortical steroid inhalants.



### **SECTION 5 : FIRE FIGHTING MEASURES :**

Suitable Extinguishing Media : Water Fog, Alcohol Foam, Dry Chemical

SAFER ALTERNATIVE TO ACID -BASED MINERAL CLEANERS **REMOVES HARD WATER STAINS** 

Unsuitable Extinguishing Media : None

Flammability : Not Flammable ( Aqueous Solution )

Flashpoint ( °F, °C, PMCC) : > 212°F

Special Hazards : Heating of mixture may produce Hydrogen Chloride (HCI) or other toxic fumes . Special Protective Equipment for Fire Fighters : Wear self-contained Respiratory Protective Device . Wear fully protective suit . Cool Endangered containers with water spray .

### SECTION 6 : ACCIDENTIAL RELEASE MEASURES

Ventilate area with fresh air . In case of unusual, excessive chemical fumes, use a respiratory protective device . Exercise caution from slipping on leaked / spilled product .

Leak and Spill Procedure : Collect excess product for disposal . Clean up remaining product from spill with appropriate liquid-binding absorbent (ie: sand, diatomite, universal binders, sawdust). For large spills, provide diking or other containment measures to prevent spreading. If diked product can be pumped, store recovered product in compatible drums for recovery or disposal . Clean area with warm water several times to prevent any future slip hazards . Observe personal protective equipment recommendations .

Environmental Precautions : Make best efforts to prevent entry into sewers and public waters. Take extreme measures to prevent large quantities of product to reach ground water, water course, or sewage system .

### SECTION 7: HANDLING & STORAGE REQUIREMENTS

### **KEEP OUT OF REACH OF CHILDREN**

Precautions for Safe Handling : Read product literature, label , and SDS before use . Use product strictly according to label directions . Wash hands and other exposed areas with soap and water before eating, drinking, smoking; or when leaving work . Provide adequate ventilation in storage area to prevent formation of fumes . Avoid personal contamination, especially inhalation, after a spill .

Hygiene Measures : Wash hands and forearms thoroughly after handling . Launder soiled, contaminated clothing before re-use .

Safe Storage Conditions : Do Not Store in Metal, especially Aluminum containers. Keep in original container in a cool, well-ventilated place. Avoid storage near near extreme heat , ignition sources or open flames . Keep container tightly sealed when not in use .

Incompatible Products : Caustic Alkalis or other caustic solutions .

Incompatible Circumstances : Sources of Ignition ( ie ; open flames ) . Direct sunlight .

## SECTION 8 : EXPOSURE CONTROLS / PERSONAL PROTECTION

Health & Safety : Derived from a blend of organic salts and degreasing agents .

This diluted, finished product used as per label directions does not contain any relevant quantities of ingredients with critical values that have to be monitored at the workplace .

Engineering Controls : Adequate general ventilation

Personal Protective Equipment : Avoid unnecessary exposure . Otherwise, acid-resistant protective work clothing .

Respiratory Protection : May not be required under normal conditions of use with good ventilation . Wear appropriate mask or respiratory protective device when misted or fogged ; or when high concentrations are present . For unplanned spills, respiratory protection may be advisable . Skin / Hand Protection : Wear chemical -resistant gloves (ie : rubber, butyl rubber, neoprene). For skin and body protection, usually no protective clothing is required under normal ,stable conditions . Under unusual, unstable conditions , wear appropriate protective clothing . Eye Protection: Wear chemical goggles or safety glasses . Avoid contact with eyes . Eye bath , safety shower should be available . Other Information : DO NOT eat, drink, or smoke during use .



## SAFER ALTERNATIVE TO ACID -BASED MINERAL CLEANERS REMOVES HARD WATER STAINS

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State : Liquid pH ( as is ) : 1.0 - 1.5 Freezing Point : < 32 °F, < 0 °C Solubility in Water : 100 % Miscible Explosive Limits : Undetermined

Partition coefficient : ( n-octanol/water ) Undetermined Auto-ignition Temperature : >500 °F/ >260 °C

Specific Gravity (Water = 1): @ 68°F ( 20°C ): 1.21

Color : Clear - Amber Relative Evaporation Rate ( butyl acetate=1 ) : NA Boiling Point : >212  $^{\circ}$  F Evaporation Rate (Ethyl Ether=1 : Undetermined Vapor Pressure : 23hPa ( 17mm Hg ) Auto ignition Tomporature : >500  $^{\circ}$ E( >260  $^{\circ}$ C

### Odor : Mild Melting Point : Undetermined Flashpoint : ≥200 <sup>°</sup> F Flammability : NA Relative Density : 1.100 Decomposition Temp. : Undetermined

### SECTION 10: STABILITY AND REACTIVITY

Reactivity: No Additional Information Available Chemical stability: Stable under Normal Condition s in temperatures not to exceed > 230 °F, > 110 °C. Possibility of Hazardous Reactions: Reacts with strong alkalis. Reacts with strong oxidizing agents. Reacts with reducing agents. Toxic fumes may be released if extremely heated. Corrosive action on metals. Small possibility of hydrochloric acid being formed in humid air.

Conditions to Avoid : Direct Sunlight . Extremely High or Low Temperatures

Incompatible Materials : Strong Acids/Strong Alkalis/Strong Oxidizing Agents

Hazardous Decomposition By-products : Chlorine gas may be released . Hydrogen chloride (HCI), carbon monoxide ; carbon dioxide; nitrogen oxides Fumes Hazardous Polymerization : NA

#### SECTION 11 : TOXICOLOGICAL INFORMATION

**Information on Toxicological Effects:** Any hazards associated with this finished product are listed in SECTION 2 of this SDS. This product is not regarded as a mutagen or carcinogen, and there is low concern for reproductive, developmental, or nervous system toxic effects. **Likely Routes of Exposure ("Mineral X"):** Inhalation, Skin Contact, Eye Contact, Ingestion.

Inhalation : Slight irritant effect on mucous membranes, if inhaled . If an allergic reaction does occur, move individual to fresh air . If breathing is irregular or stopped, administer artificial respiration. In case of shortness of breath, give oxygen. Call a physician immediately. Skin Contact : May be irritating with prolonged contact . In extreme cases , if "Redness" or Sensitization occurs through direct skin contact , seek

Skin Contact : May be irritating with prolonged contact . In extreme cases , if "Redness " or Sensitization occurs through direct skin contact , seek the attention of a physician immediately .

Eye Contact : Irritating Effect May Occur Through Direct Contact . In extreme cases , if "redness" and watering of eyes persists , seek the attention of a physician immediately .

Ingestion :Swallowing will lead to a caustic effect on mouth and throat ; and to the danger of perforation of esophagus and stomach .

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics : Breathing difficulty, coughing, cramp, nausea, acidosis, disorientation. Extreme caution regarding gastric perforation; pulmonary edema; impaired breathing; & disturbed cardiac rhythm. Potential symptoms of poisoning may occur after several hours of exposure. It is advised that at least 48 hour medical observation take place after the incident, especially for pneumonia and pulmonary edema. In case of irritation to lungs, initially treat with cortical steroid inhalants.

#### Acute Toxicity , Toxicological (see table below)

**Measures of Acute Toxicity by Ingredients :** The following Acute Toxicity Estimates (ATE) are calculated on this GHS document. Toxicological Data of complete product are not available. No classification on the basis of the calculation procedure of the preparation directive. Data not available or is insufficient for classification. The toxicity data listed pertaining to the ingredients are intended for those working in the medical professions, experts for occupational health and safety, and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials. This finished product used as per label directions is not considered to be a harmful in the workplace by IARC, ACGIH, NTP, or OSHA.

MINERAL X page 4



## SAFER ALTERNATIVE TO ACID -BASED MINERAL CLEANERS REMOVES HARD WATER STAINS

Product / Ingredient Name :	Result :	Species :	Exposure :
Carbamide (Urea) Hydrochloride			
(cas # 506-89-8)	LD 50 Acute Dermal	Rabbit	> 2000 mg/kg
	LD 50 Acute Oral	Rat	> 1100 mg/kg

Symptoms Related To The Physical, Chemical and Toxicological Characteristics : Symptoms may include stinging, tearing, redness, swelling, and blurred vision. After extensive, prolonged exposure, permanent eye damage including blindness could result. Available Delayed and Immediate Effects ( Chronic Effects from Short and Long Term Exposure ) : Warning after prolonged , extended skin absorption . toxic and / or corrosive effects may be delayed up to 48 hours after use . Measures of Acute Toxicity ("Mineral X"): No Further Information Available Teratogenicity, Mutagenicity ("Mineral X"): This product was not found to be mutagenic when tested by the Ames Assay, (OECD Guidellines for Testing of Chemicals, Section 471). Reproductive Toxicity ("Mineral X"): This product was not found to effect human reproduction when tested by the Ames Assay, (OECD Guidellines for Testing of Chemicals, Section 471) Specific Target Organ Toxicity (Single Exposure) ( "Mineral X "): Not Classified Specific Target Organ Toxicity ( Repeated Exposure ) ( " Mineral X " ) : Not Classified Carcinogenic Categories : None of the Ingredients are listed Carcinogenicity: CAS# 506 - 89 - 8 : Non-hazardous by WHMIS / OSHA Criteria . ACGIH : Not listed IARC : Not Listed NTP : Not listed Epidemiology : No human information available. Neurotoxicity : No information available. Aspiration Hazard : Not Classified Potential Adverse Human Health Effects & Symptoms : Based on Available Data, the Classification Criteria are not met Symptoms / Injuries After Inhalation : No adverse effects due to inhalation are expected. Symptoms / Injuries After Skin Contact : After Prolonged Exposure, May Cause Serious Skin Irritation Symptoms / Injuries after Eye Contact : After Prolonged Exposure, May Cause Serious Eye Damage

### SECTION 12 : ECOLOGICAL INFORMATION

ENVIRONMENTAL ACCREDITATION : This diluted, finished product used as per label directions is not considered to be a harmful to human life or the environment.

ECOTOXICITY: The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and Degradability : Based on the biodegradability data of the components, this material is expected to be biodegradable.

Bioaccumulative Potential : This material does not contain chemicals that have known bioaccumulative potential.

Other adverse effects : No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Chemical Name :	Result :	Species :	Exposure :
Carbamide(Urea) Hydrochloride (cas # 506-89-8)	Acute LC 50	Daphnia	71 mg/ L ,48 hrs .



SAFER ALTERNATIVE TO ACID -BASED MINERAL CLEANERS REMOVES HARD WATER STAINS

" Mineral X " as a finished p	roduct :
Persistance and Degradability	Not Established

BIOACCUMULATIVE POTENTIAL : " Mineral X " as a finished product ......Not Established

TERRESTRIAL TOXICITY ( " Mineral X " ) :	No Additional Information Available
MOBILITY IN SOIL ( " Mineral X " ) :	No Additional Information Available
OTHER ADVERSE EFFECTS :	
Effect on Ozone Layer ( " Mineral X " )	No Additional Information Available
Effect on Global Warming ( " Mineral X " )	No Additional Information Available

#### SECTION 13 : DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations : Dispose in safe manner in accordance with local / state/federal regulations . Dispose of contents / container in accordance with local / regional / national / international regulations . Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities while adhering to the necessary regulations . Ecology – Waste Materials : Avoid release into environment . Recommended Cleansing Agents : Water Only

#### **SECTION 14: TRANSPORT INFORMATION**

### SECTION 15 : REGULATORY INFORMATION

Safety, Health, and Environmental Regulations/Legislation specific for the substance or mixture. the ingredients of this product are NOT subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act. U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for any ingredients of this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lbs. (4,540 kg) therefore applies, per 40 CFR 370.20.

MINERAL X page 6



## SAFER ALTERNATIVE TO ACID -BASED MINERAL CLEANERS **REMOVES HARD WATER STAINS**

## **REGULATORY INFORMATION (continued)**

CANADIAN DSL/NDSL INVENTORY STATUS : The components of this product are listed on the DSL Inventory. CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS : No component of this product is on the CEPA Priority Substances Lists.



SAFER ALTERNATIVE TO ACID -BASED MINERAL CLEANERS REMOVES HARD WATER STAINS

#### **SECTION 16: OTHER INFORMATION**



DISCLAIMER : This document is intended to provide a brief summary of our present knowledge and guidance regarding the use of this material . The information set forth herein has been compiled from sources to be dependable and is believed to be accurate as of the date of issuance . This information is offered in good faith by HEALTHY CLEAN BUILDINGS and no warranty, expressed or implied, is made . The user assumes all liability for any damage or injury resulting from misuse, from any failure to adhere to recommended practices according to product label ( and such ), or from any hazards inherent in the nature of the product . This document shall not constitute a guarantee for any specific product features and shall not establish a legally valid contracted relationship.

Footnotes : CALC-Calculated; COR-Corrosive; CS-Cancer Suspect Agent; EST-Estimated; HMIS-Hazardous Material Identification System; NA-Not Applicable; ND-No Data ; NE – Data Not Established; OX- Oxidizer; PEL-Permissible Exposure Limit; PPI-Personal Protection Index ; STEL-Short Time Exposure Limit; TLV-Threshold Limit Value; TWA-Time Weighted Average